§ 60.5421

since the original vessel was first located at the site, including the days when the storage vessel was removed, will be added to the count towards the number of consecutive days.

- (6) For each storage vessel or centrifugal compressor subject to the closed vent system inspection requirements of $\S60.5416(a)(1)$ and (2), records of each inspection.
- (7) For each storage vessel or centrifugal compressor subject to the cover requirements of §60.5416(a)(3), a record of each inspection.
- (8) For each storage vessel or centrifugal compressor subject to the bypass requirements of §60.5416(a)(4), a record of each inspection or a record each time the key is checked out or a record of each time the alarm is sounded.
- (9) For each closed vent system used to comply with this subpart that must operate with no detectable emissions, a record of the monitoring conducted in accordance with §60.5416(b)(13).
- (10) Records of the schedule for carbon replacement (as determined by the design analysis requirements of §60.5413(c)(2) or (3)) and records of each carbon replacement as specified in §60.5412(c)(1).
- (11) For each storage vessel or centrifugal compressor subject to the control device requirements of §60.5412, records of minimum and maximum operating parameter values, continuous parameter monitoring system data, calculated averages of continuous parameter monitoring system data, results of all compliance calculations, and results of all inspections.

§ 60.5421 What are my additional recordkeeping requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?

- (a) You must comply with the requirements of paragraph (b) of this section in addition to the requirements of §60.486a.
- (b) The following recordkeeping requirements apply to pressure relief devices subject to the requirements of §60.5401(b)(1) of this subpart.
- (1) When each leak is detected as specified in §60.5401(b)(2), a weather-proof and readily visible identification, marked with the equipment identifica-

- tion number, must be attached to the leaking equipment. The identification on the pressure relief device may be removed after it has been repaired.
- (2) When each leak is detected as specified in §60.5401(b)(2), the following information must be recorded in a log and shall be kept for 2 years in a readily accessible location:
- (i) The instrument and operator identification numbers and the equipment identification number.
- (ii) The date the leak was detected and the dates of each attempt to repair the leak.
- (iii) Repair methods applied in each attempt to repair the leak.
- (iv) "Above 500 ppm" if the maximum instrument reading measured by the methods specified in paragraph (a) of this section after each repair attempt is 500 ppm or greater.
- (v) "Repair delayed" and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.
- (vi) The signature of the owner or operator (or designate) whose decision it was that repair could not be effected without a process shutdown.
- (vii) The expected date of successful repair of the leak if a leak is not repaired within 15 days.
- (viii) Dates of process unit shutdowns that occur while the equipment is unrepaired.
- (ix) The date of successful repair of the leak.
- (x) A list of identification numbers for equipment that are designated for no detectable emissions under the provisions of 60.482-4a(a). The designation of equipment subject to the provisions of 60.482-4a(a) must be signed by the owner or operator.

§ 60.5422 What are my additional reporting requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?

- (a) You must comply with the requirements of paragraphs (b) and (c) of this section in addition to the requirements of \$60.487a(a), (b), (c)(2)(i) through (iv), and (c)(2)(vii) through (viii).
- (b) An owner or operator must include the following information in the initial semiannual report in addition to